

Silicon N-Channel Power MOSFET

Description


The TH20N65PC uses advanced technology and design to provide excellent $R_{DS(ON)}$. The transistor can be used in various power switching circuit for system miniaturization and higher efficiency.

General Features

- $V_{DS}=650V, I_D=20A$
- Low ON Resistance
- Low Reverse transfer capacitances
- 100% Single Pulse avalanche energy Test

Application

- Power switching application



Electrical Characteristics @ $T_a=25^\circ\text{C}$ (unless otherwise specified)

a) Absolute Maximum Ratings:

Symbol	Parameter	Value	Units
V_{DSS}	Drain-to-Source Breakdown Voltage	650	V
I_D	Drain Current (continuous) at $T_c=25^\circ\text{C}$	20	A
I_{DM}	Drain Current (pulsed)	80	A
V_{GS}	Gate to Source Voltage	+/-30	V
P_{tot}	Power Dissipation at $T_c=25^\circ\text{C}$	250	W
	Derating Factor above 25°C	2.0	W/ $^\circ\text{C}$
T_j	Max. Operating Junction Temperature	175	$^\circ\text{C}$
E_{AS}	Single Pulse Avalanche Energy	1200	mJ

b) Electrical Parameters:

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
V_{DS}	Drain-source Voltage	$V_{GS}=0V, I_D=250\mu A$	650			V
$R_{DS(on)}$	Static Drain-to-Source on-Resistance	$V_{GS}=10V, I_D=10A$		0.37	0.5	Ω
$V_{GS(th)}$	Gated Threshold Voltage	$V_{DS}=V_{GS}, I_D=250\mu A$	2.0		4.0	V
I_{DSS}	Drain to Source leakage Current	$V_{DS}=600V, V_{GS}=0V$			1.0	μA
$I_{GSS(F)}$	Gated to Source Forward Leakage	$V_{GS}=+30V$			100	nA
$I_{GSS(R)}$	Gated to Source Reverse Leakage	$V_{GS}=-30V$			-100	nA
C_{iss}	Input Capacitance	$V_{GS}=0V,$ $V_{DS}=25V,$ $f=1.0MHz$		2400		pF
C_{oss}	Output Capacitance			225		pF
C_{rss}	Reverse Transfer Capacitance			20		pF

c) Switching Characteristics

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
$t_{d(on)}$	Turn-on Delay Time	$V_{DD}=325V, I_D=20A,$ $R_G=25\Omega$		35		nS
t_r	Turn-on Rise Time			82		nS
$t_{d(off)}$	Turn-off Delay Time			180		nS
t_f	Turn-off Fall Time			90		nS
Q_g	Total Gate Charge	$V_{DS}=325V$ $I_D=20A$ $V_{GS}=10V$		65		nC
Q_{gs}	Gate-Source Charge			11		nC
Q_{gd}	Gate-Drain Charge			26		nC


d) Source-Drain Diode Characteristics

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
I _{SD}	S-D Current(Body Diode)				20	A
I _{SDM}	Pulsed S-D Current(Body Diode)				80	A
V _{SD}	Diode Forward Voltage	V _{GS} =0V, I _{DS} =20A			1.5	v
t _{rr}	Reverse Recovery Time	T _J =25 °C, I _S =20A di/dt=100A/us		390		nS
Q _{rr}	Reverse Recovery Charge			3.4		μC
	*Pulse Test: Pulse Width <= 300μs, Duty Cycle< =2%					

Symbol	Parameter	Typ	Units
$R_{\theta JC}$	Junction-to-Case	0.5	$^\circ C/W$
$R_{\theta JA}$	Junction-to-Ambient	40	$^\circ C/W$

Package Information

TO-220C PACKAGE



Symbol	单位 mm		
	Min	Nom	Max
A	4.30	4.5	4.70
A1	1.20	1.30	1.40
A2	2.20	2.4	2.60
b	0.60	0.8	1.00
b1	1.20	1.30	1.40
c	0.40	0.5	0.60
e	2.44	2.54	2.64
E	9.80	10.0	10.2
E1	8.50	8.70	8.90
H	15.5	15.7	15.9
H1	9.00	9.2	9.40
H2	1.10	1.34	1.50
H3	1.50	1.7	1.90
H4	12.9	13.3	13.7
H5	2.80	3.0	3.20
G	2.60	2.8	3.00
ΦP	3.40	3.6	3.80

Notice

Thunder Microelectronics Incorporated Limited reserves the right to make changes without further notice to any products or specifications herein. When use the product, be sure to obtain the latest specification.

Thunder Microelectronics Incorporated Limited does not assume any liability arising out of the application or any product described herein. When using Thunder Microelectronics Incorporated Limited products in your equipment, you are requested to take adequate safety measures to prevent the equipment from causing a physical injury ,fire or other problem if any of the products become faulty.

-Headquarters

WuXi Thunder Microelectronics Incorporated Limited

Building E1-9L, No.200 LingHu Road, XinWu district,WuXi,China 214135

Tel:+86-510-85160109

Fax:+86-510-85160109