

Silicon N-Channel Power MOSFET

Description


The TH3N150PH uses advanced technology and design to provide excellent $R_{DS(ON)}$. It can be used in a wide variety of applications.

General Features

- $V_{DS}=1500V, I_D=3A$
- Low ON Resistance
- Low Reverse transfer capacitances
- 100% Single Pulse avalanche energy Test

Application

- Power switching application
- Adapter and charger



Electrical Characteristics @ $T_a=25^\circ C$ (unless otherwise specified)

a) Absolute Maximum Ratings:

Symbol	Parameter	Value	Unit
V_{DSS}	Drain-to-Source Breakdown Voltage	1500	V
I_D	Drain Current (continuous) at $T_c=25^\circ C$	3	A
I_{DM}	Drain Current (pulsed)	12	A
V_{GS}	Gate to Source Voltage	+/-30	V
P_{tot}	Total Dissipation at $T_c=25^\circ C$	186	W
T_j	Max. Operating Junction Temperature	150	$^\circ C$
E_{AS}	Single Pulse Avalanche Energy	125	mJ

b) Electrical Parameters:

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
V_{DS}	Drain-source Voltage	$V_{GS}=0V, I_D=250\mu A$	1500			V
$R_{DS(on)}$	Static Drain-to-Source on-Resistance	$V_{GS}=10V, I_D=1.5A$		5.2	9.0	Ω
$V_{GS(th)}$	Gated Threshold Voltage	$V_{DS}=V_{GS}, I_D=250\mu A$	3.0		5.0	V
I_{DSS}	Drain to Source leakage Current	$V_{DS}=1500V, V_{GS}=0V$			1	μA
$I_{GSS(F)}$	Gated to Source Foward Leakage	$V_{GS}=+30V$			100	nA
$I_{GSS(R)}$	Gated to Source Reverse Leakage	$V_{GS}=-30V$			-100	nA
C_{iss}	Input Capacitance	$V_{GS}=0V,$ $V_{DS}=25V,$ $f=1.0MHZ$		1938		pF
C_{oss}	Output Capacitance			5104		pF
C_{rss}	Reverse Transfer Capacitance			2.4		pF

c) Switching Characteristics

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
$t_{d(on)}$	Turn-on Delay Time	$V_{DD}=750V, I_D=3A,$ $R_G=10\Omega$		33.8		nS
t_r	Turn-on Rise Time			16.7		nS
$t_{d(off)}$	Turn-off Delay Time			56		nS
t_f	Turn-off Fall Time			27.6		nS
Q_g	Total Gate Charge	$V_{DS}=750V$ $I_D=3A$ $V_{GS}=10V$		9.3		nC
Q_{gs}	Gate-Source Charge			174.9		nC
Q_{gd}	Gate-Drain Charge			5.3		nC


d) Source-Drain Diode Characteristics

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
I _{SD}	S-D Current(Body Diode)				3	A
I _{SDM}	Pulsed S-D Current(Body Diode)				12	A
V _{SD}	Diode Forward Voltage	V _{GS} =0V, I _{DS} =3A			1.5	V
t _{rr}	Reverse Recovery Time	T _J =25℃, I _F =3A di/dt=100A/us		302.3		nS
Q _{rr}	Reverse Recovery Charge			9.9		nC
	*Pulse Test: Pulse Width <= 300μs, Duty Cycle< =2%					

Symbol	Parameter	Typ	Unit
$R_{\theta JC}$	Junction-to-Case	0.67	$^\circ C/W$

Package Information

TO-3PH PACKAGE



Symbol	单位 mm		
	Min	Nom	Max
A	5.35	5.55	5.75
A1	2.80	3.00	3.20
A2	1.90	2.10	2.30
A3	1.10	1.30	1.50
b	0.65	0.75	0.85
b1	1.80	2.00	2.20
b2	1.80	2.00	2.20
c	0.70	0.90	1.10
e	5.25	5.45	5.65
E	15.3	15.5	15.7
E1	9.80	10.0	10.2
E2	3.80	4.00	4.20
H	24.3	24.5	24.7
H1	9.00	9.20	9.40
H2	15.1	15.3	15.5
H3	18.5	19.0	19.5
H4	1.80	2.00	2.20
H5	4.80	5.00	5.20
G	4.3	4.5	4.7
ΦP	3.40	3.60	3.80

Notice

Thunder Microelectronics Incorporated Limited reserves the right to make changes without further notice to any products or specifications herein. When use the product, be sure to obtain the latest specification.

Thunder Microelectronics Incorporated Limited does not assume any liability arising out of the application or any product described herein. When using Thunder Microelectronics Incorporated Limited products in your equipment, you are requested to take adequate safety measures to prevent the equipment from causing a physical injury ,fire or other problem if any of the products become faulty.

-Headquarters

WuXi Thunder Microelectronics Incorporated Limited

Building E1-9L, No.200 LingHu Road, XinWu district,WuXi,China 214135

Tel:+86-510-85160109

Fax:+86-510-85160109