

Silicon Trench NPT IGBT

Description


The THG20T65NQF is use advanced trench NPT technology.
The 650V NPT Trench IGBT offers superior conduction and switching performances.

General Features

- High Speed Switching & Low Power Loss
- Low saturation voltage: $V_{CE(sat)} = 1.95V @ I_C = 20A$
- $E_{off} = 0.6mJ @ T_C = 25^{\circ}C$
- Maximum junction temperature $175^{\circ}C$

Application

- Solar Converters
- Welding Converters
- UPS
- PFC
- PV Inverter



Absolute Maximum Ratings @ $T_C=25^{\circ}C$ (unless otherwise specified)

Symbol	Parameter	Value	Units
V_{CES}	Collector-Emitter Voltage	650	V
V_{GES}	Gate-Emitter Voltage	± 20	V
I_C	Collector Current	40	A
	Collector Current @ $T_C=100^{\circ}C$	20	A
I_{CM}	Pulsed Collector Current	60	A
I_F	Diode Continuous Forward Current @ $T_C=100^{\circ}C$	20	A
I_{FM}	Pulsed Diode Forward Current	60	A
P_D	Total Dissipation at @ $T_C = 25^{\circ}C$	125	W
	Total Dissipation at @ $T_C = 100^{\circ}C$	62.5	
T_j	Operating Junction and Storage Temperature Range	-55 to +175	$^{\circ}C$
T_L	Max Temperature For Soldering	260	$^{\circ}C$
T_{SC}	Short circuit withstand time $V_{GE}=15V, V_{CC} \leq 400V$, Allowed number of short circuits < 1000 Time between short circuits: $\geq 1.0s, T_j \leq 150^{\circ}C$	5	us

Electrical Characteristics @ T_c=25°C (unless otherwise specified)

Symbol	Parameter	Test Conditions		Min	Typ	Max	Unit
Static Characteristics							
V _{CES}	Collector-Emitter Voltage	V _{GE} =0V, I _{CE} =250μA		650	—	—	V
V _{CE(sat)}	Collector-Emitter Saturation Voltage	V _{GE} =15V, I _C =20A	T _j = 25°C	—	1.95	2.50	V
			T _j = 175°C	—	2.15	—	V
V _{GE(th)}	Gated Threshold Voltage	V _{CE} =V _{GE} , I _C =0.5mA		4.8	5.7	6.6	V
I _{CES}	Collector-Emitter Leakage Current	V _{GE} =0V, V _{CE} =650V		—	—	10	uA
I _{GES(F)}	Gate to Emitter Forward Leakage	V _{GE} = +20V, V _{CE} = 0V		—	—	200	nA
I _{GES(R)}	Gate to Emitter Reverse Leakage	V _{GE} = -20V, V _{CE} = 0V		—	—	-200	nA
Dynamic Characteristics							
C _{ies}	Input Capacitance	V _{GE} =0V, V _{CE} =25V, f=1.0MHZ		—	1200	—	pF
C _{oes}	Output Capacitance			—	90	—	pF
C _{res}	Reverse Transfer Capacitance			—	15.1	—	pF
Q _g	Total Gate Charge	V _{CE} =480V, I _C =20A, V _{GE} =15V		—	72	—	nC
Q _{ge}				—	12	—	
Q _{gc}				—	37	—	
Switching Characteristics							
t _{d(on)}	Turn-on Delay Time	V _{CE} =400V, I _C =20A V _{GE} =15V, R _G =10Ω		—	30	—	nS
t _r	Rise Time			—	24	—	
t _{d(off)}	Turn-off Delay Time			—	170	—	
t _f	Fall Time			—	22	—	
E _{on}	Turn-on Switching Loss						0.221
E _{off}	Turn-off Switching Loss				0.586		

Electrical Characteristics of the Diode @T_C= 25°C unless otherwise specified

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
I _F	Diode Continuous Forward Current	T _C = 100°C	20	—	—	A
I _{FM}	Pulsed Diode Forward Current	T _C = 25°C	60	—	—	A
V _F	Diode Forward Voltage	I _F =20A	—	1.6	2.4	V
t _{rr}	Reverse Recovery Time	T _J =25°C, I _F =20A di/dt=200A/us	—	80	—	nS
Q _{rr}	Reverse Recovery Charge		—	4.9	—	nC
*Pulse Test: Pulse Width <= 300μs, Duty Cycle< =2%						

Thermal Characteristic

Symbol	Paramter	Typ	MAX	Units
$R_{\theta JC}$	Thermal Resistance,Junction to case for IGBT	--	1.2	$^{\circ}\text{C}/\text{W}$
$R_{\theta JA}$	Thermal Resistance,Junction to Ambient	--	59.5	$^{\circ}\text{C}/\text{W}$

Typical Performance Characteristics




Figure1: typical IGBT output characteristics,
TC=25°C




Figure2: typical IGBT output characteristics
TC=125°C




Figure3: typical VCE VS. VGE, TJ=25°C




Figure4: typical diode forward characteristic




Figure 5: typical capacitance VS. VCE, VGE=0V, f=100kHz




Figure 6 : typical gate charge VS. VGE, IC=15A




Figure 7 : typical energy loss VS. IC, TC=25°C,

L=500uH, VCE=400V, VGE=15V, Rg=10Ω




Figure 8 : typical switching time VS. IC, TC=25°C,

L=500uH, VCE=400V, VGE=15V, Rg=10Ω




Figure 9 : typical energy loss VS. IC, TC=125°C,
L=500uH , VCE=400V,VGE=15V,Rg=10Ω




Figure10: typical switching time VS. IC, TC=125°C,
L=500uH, VCE=400V,VGE=15V,Rg=10Ω




Figure11: typical energy loss VS. Rg,TC=25°C,
L=500uH, VCE=400V, VGE=15V, IC=15A








Figure12: typical switching time VS. Rg,TC=25°C,
L=500uH,VCE=400V,VGE=15V,IC=15A



Package Information

TO-220F PACKAGE

基本尺寸



Symbol	单位 mm		
	Min	Nom	Max
A	4.55	4.75	4.95
A1	2.40	2.60	2.80
A2	0.40	0.60	0.80
A3	2.10	2.30	2.50
b1	1.10	1.30	1.50
b	0.60	0.80	1.00
c	0.42	0.50	0.58
e	2.30	2.50	2.70
E	9.9	10.1	10.3
E1	6.8	7	7.2
H	15.8	16.0	16.2
H1	9.10	9.30	9.50
H2	12.5	13.0	13.5
H3	3.10	3.30	3.50
G	3.00	3.20	3.40
ΦP	3.00	3.20	3.40

Notice

Thunder Microelectronics Incorporated Limited reserves the right to make changes without further notice to any products or specifications herein. When use the product, be sure to obtain the latest specification.

Thunder Microelectronics Incorporated Limited does not assume any liability arising out of the application or any product described herein. When using Thunder Microelectronics Incorporated Limited products in your equipment, you are requested to take adequate safety measures to prevent the equipment from causing a physical injury ,fire or other problem if any of the products become faulty.

-Headquarters

WuXi Thunder Microelectronics Incorporated Limited

Building E1-9L, No.200 LingHu Road, XinWu district, WuXi, China 214135

Tel:+86-510-85160109

Fax:+86-510-85160109